Observations from Confirmation Testing of Advanced Technologies Recommended under NCAP

Clarke Harper

Crash Avoidance NCAP coordinator

John Lee, Glenn Gamber and Kellen Shain

SAE Government Industry Meeting, Jan 30, 2013



U.S. Department of Transportation

National Highway Traffic Safety

Administration





Background

- Model Year 2010 –NHTSA conducts tests of vehicles that reportedly comply with the NCAP procedure; testing validates NCAP test procedures.
- Model Year 2011 Advanced Crash Avoidance Technologies added to NHTSA's New Car Assessment Program (NCAP)
 - Lane Departure Warning (LDW), Forward Collision Warning (FCW), Electronic Stability Control (ESC) – "recommended" to consumers with check mark on <u>www.safercar.gov</u> (<u>ESC not</u> discussed here)
 - Recommendations requires manufacturers submitted test data showing that they pass NHTSA test procedure
 - NHTSA conducts spot check tests of vehicles for which manufacturer has submitted data, failure results in removal of recommendation

Program Basics

- Self-verification by manufacturers
- Data submitted annually in writing to NHTSA
- Data Reviewed by NHTSA staff
- "Recommended" Icons added to SaferCar.gov







- ▶ Confirmation testing conducted by NHISA
- Failure will result in "recommended" removed
- ESC has been on all vehicles since MY 2011


Program Clarifications


- "2-consecutive-failures" deleted from FCW TP
 - Now: pass 5 out of seven trials, any order.
- ▶ LDW and FCW pass if ANY warning is on time.
- CAN Bus data as a warning method will be dropped in MY 2015.

"Recommended" on SaferCar.gov



Market Response






Testing Issues

Misinterpretation of Test Procedure by Non-NHTSA Labs

Independent Test Lab Track line layout wrong in non-NHTSA report; lane is 2 ½ feet too wide.



Actual Warnings vs. CAN Bus Data

- The agency uses actual audio, visual or haptic signals
- Some manufacturers are using only CAN (controller area network) data
 - CAN bus codes have all been confidential
 - CAN bus codes are not readily provided by vehicle manufacturers
- CAN bus was only intended to be used if access to the actual signals was difficult
- NCAP will be deleting the use of CAN bus codes in FCW and LDW







Vehicle-related Issues


Initial Self-Calibration Forward Collision Warning Systems

- Some vehicles not warning when delivered.
 - Self-calibration of radar unit is built into vehicle programming
 - Requires up to 100 miles of driving to calibrate before they completely pass FCW Test 1, "lead vehicle stopped".



Algorithm Confusion, LDW

- Track conditions confused some LDW systems.
 - Lanes too close together
 - Track surface conditions blamed for LDW failure "construction zone"





Bott Dots

Some vehicle LDW systems do not recognize "Bott Dots" as a lane marker.



FCW system that goes "blind"

- One vehicle system stopped working in between runs.
- The algorithm will stop warning if the system thinks it is "blind."
 - Intended to respond to blocked radar (mud, snow)
 - Will reset on ignition cycle or if targets reappear.
 - During testing, pointed the car at a target while idling between tests to alleviate issue; passed test.

Summary

- Manufacturer's participation in the Crash Avoidance NCAP program went from significantly increasing.
- Number of models that had advanced technologies went from 7% in MY2011 to 25% in MY2013.
- Algorithm designs are the source of most performance issues.
- "Problems" appear to be unique to individual manufacturers.